UNCLASSIFIED

AD NUMBER AD842837 **NEW LIMITATION CHANGE** TO Approved for public release, distribution unlimited **FROM** Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; NOV 1968. Other requests shall be referred to the U. S. Army Electronics Command, Fort Monmouth, New Jersey. **AUTHORITY** st-a usaec notice, 13 Sep 1971

THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTPOLS AND EACH TRANSMITTAL TO PORTION COVERNMENTS OR FORTION NATIONALS MAY BE MADE ONLY WITH PPIOR APPROVAL OF ATMOSPHERIC SCIENCES RESEARCH OFFICE, HITT STILL RANCE, NEW MEXICO.

INTERPOROLOGICAL PATA REPORT


TIKE-HYDAC STV, SR-076 (10 October 1968)


3¥

LEN E. CARTER

ATMOSPHERIC SCIENCES RESEARCH OFFICE WHITE SANDS MISSILE RANGE, NEW MEXICO







DISPOSITION INSTRUCTIONS.

Destroy this report when it is no longer needed. Do not return it to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorised documents.

The citation of trade names and names of mamufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV, SR-076 (10 October 1968)

Ву

Len E. Carter

DR-369

November 1968

DA Task 1T665702D127-02

ATMOSPHERIC SCIENCES RESEARCH OFFICE WHITE SANDS MISSILE RANGE, NEW MEXICO

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atmospheric Sciences Research Office, White Sands Missile Range, New Mexico.

ABSTRACT

Meteorological data gathered for the launching of Nike-Hydac STV, SR-076, are presented for the Space and Missile Systems Organization, Greenbelt, Maryland, and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

		PAGE
ABSTRAC	· · · · · · · · · · · · · · · · · · ·	iii
INTRODU	ICTION	1
DISCUSS	жини и жи	1
TABLES		
ı.	Theoretical Rocket Performance Values	2
II.	Ballistic Factors	3
III.	Amemometer Wind Speed and Direction	4
IV.	Pilot-Balloon-Measured Wind Data	5
v.	Rawinsonde-Measured Wind Data	6
VI.	Significant Level Data (Release Time: 0330 MDT)	7
VII.	Upper Air Data (Release Time: 0330 MDT)	8
VIII.	Mandatory Levels (Release Time: 0330 MDT)	15
IX.	Significant Level Data (Release Time: 0630 MDT)	16
x.	Upper Air Data (Release Time: 0630 MDT)	17
XI.	Mandatory Levels (Release Time: 0630 MDT)	24
XII.	Impact Prediction Data	25

INTRODUCTION

Nike-Hydac STV, SR-076, was launched from LC-33, L-314, White Sands Missile Range (WSMR), New Mexico, at 0630 hours MDT, 10 October 1968.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Technical Area, U. S. Army Electronics Research and Development Activity, WSMR, New Mexico. The Ballistic Meteorologists for this firing were Gordon L. Dunaway and Len E. Carter.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of five Aerovanes mounted on a 200-foot tower and cabled to wind component indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from T-9 Radar-tracked balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 100,000 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and wind-weighting values as a function of altitude were provided by the Meteorological Support Technical Area, WSMR, New Mexico, and are the basis for the data appearing in Table I.

PAYLOAD		223	Pounds
CORIOLIS DISFLACEMENT	WEST.	6"7	Miles
יווסדייווסד מסגמס מווססמס	TIME	20.0	Seconds
SECOND-SIAGE IGNITION	ALTITODE	35,760	Feet MSL
	TIME	236	Seconds
FEAK	ALTITUDE	716,000	Feet MSL
	неал	2.51	Miles/MFH
UNIT WIND EFFECT	CROSS	2.60	Miles/MPH
	TAIL	2,52	намуветты
TOWER TILT EFFECT		14.53	Miles/Degree

TABLE I. THEORETICAL ROCKET FERFORMANCE VALUES NIKE-HYDAC STV, SR-076

BALLISTIC FACTORS	.063	990.	.035	.028	.014	.005	003	014	017	016
LAYERS IN FEET ABOVE GROUND	1000- 1400	1400- 2000	2000- 2500	2500- 3000	3000- 3500	3500- 4000	4000- 4160	4160- 9000	9000-15000	15000-21000
BALLISTIC FACTORS	.126	,084	.053	.041	.026	.062	.058	.072	.058	680.
LAYERS IN FEET ABOVE GROUND	15- 60	60- 108	108- 148	148- 184	184~ 216	216- 300	300- 400	400- 600	008 -009	800-1000

BALLISTIC FACTORS

LAYERS IN FEET ABOVE GROUND

-.013

21000-26000

-.016

26000-31770

.129

31,70-36000

.010

51000-56000

.015

46000-51000

.026

41000-46000

.057

36000-41000

900.

56000-6100

.002

66000-69330

.004

61000-66000

TABLE II. BALLISTIC FACTORS NIKE-HYDAC STV, SR-076

			62				
	; MDT	E-W	6.0E	14.0	16 0	16.0	16.0
	10K 0E90	S-N	30.6	10.0	8.0	8.0	8.0
	5 MDT	E-W	7,0E	10.0 10.0	16.0	16.0	16.0
HOUR	2 0620 NDT	S-N	80°E	4.0	3.0	4.0	4.0
MEAN WIND COMPONENTS IN MILES PER HOUR	4 NDT	M-A	4.0E	10.0	13,0	13.0	13.0
TIM NI	4 0610 NDT	N-S	3.08	3.0	5.0	6.0	6.0
PONENTS	3 MDT	M-I	8. OE	8.0	8.0	8.0	8.0
END COM	3 0545 MDT	S-N	4.0S	7.0	0.9	7.0	6.0
MEAN W.	2 MDT	E-W	2.0E	4 0	6.0	5.0	5.0
	2 0530 MDT	N-S	2.08	4 0	4.0	5.0	5.0
	1 NDT	E-W	0.0	0.0	2.0E	3.0	3.0
	1 0520 NDT	N-S	0.0	2.08	3.0	0 7	4,0
Si di	VANE NO. *		Т	N.	· m	7	72

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION NIKE-HYDAC STV, SR-076

		•											
	6 NDT	E-W	16.0E	16.5	18.5	. 17.5	15.5	0.9	2.0	1.0	2.0	7.0	4.5
	6 0630 MDT	N-S	8.58	10.5	12.5	13.5	12.0	0.9	4.5	7.0	13.0	17.0	15.0
	5 MDT	M-E	16.5E	17.0	17.0	14.5	12.0	5.5	2.0	2.5	5.0	4.0	2.0
HOUR	5 0620 MDT	N-S	4.58	5.5	8.0	9.5	5.5	2.0	3.5	8.5	14.5	16.5	12.0
IN MILES PER HOUR	4 0610 MDT	M-E	13.05	12.5	13.5	10.5	7.0	5.0	1.0	2.0	6.5	7.0	1.5
	0190	S-N	6.58	7.0	8.0	7.5	3.0	2.5	4.5	10.5	16.0	17.0	16.0
MPONENT	3 0545 MDT	M3	7.5E	7.0	0,9	6.0	6.0	5.0	3.0	3.0	5.0	5.0	2.0
MEAN WIND COMPONENTS	0545	S-N	9.08	5.5	5.0	4.0	2.5	5.0	10.0	11.5	19.0	21.0	18.0
MEAN	2 MDT	E-W	4.5E	4.0	2.5	2.5	3.5	1.0	1.0	2.5	0.9	6.5	0.5
	2 0530 MDT	N-S	2.05	5.0	5.0	5.5	6.0	0.9	9.5	13.5	20.0	19.0	19.0
	1 MDT	E-W	3.5E	5.5	3.5	2.0	3.0	2.5	1.0W	2.5E	0.9	7.5	4.5
	1 0520 MDT	N-S	5.08	6.5	0.6	8.0	6.0	3.0	7.0	12.5	1.8.5	16.5	16.0
	LAYERS IN FEET ABOVE	GROUND	216- 300	300- 400	400 - 600	900- 800	800-1000	1000-1400	1400-2000	2000-2500	2500-3000	3000-3500	3500-4000

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA NIKE-HYDAC STV, SR-076

		MEAN WIND		COMPONENTS	IN KNOTS	စ္ခ
TEET TEET ABOVE	0330	1 0330 MDT	0630	2 0630 NDT		
GINDONID	S-N	M-I	S-N	W-A	N-S	M-II
4000- 4160	8°°0S	0.0	30°7T	2.5		
4160- 9000	12.0	7.0W	16.0	%0.9		
9000-15000	7.0	1.9.5	11.0	19.0		
15000-21000	12.5	21.5	13.5	23.5		
21000-26000	10.01	27.0	18.0	31.0		
26000-31770	16.0	44.0	14.0	38.5		
31770-36000	10.0	56.0	10.5	59.0		
36000-41000	0.6	52.0	10.0	56.0		
41000-46000	8.5	47.5	0.6	21.0		
46000-51000	0.0	38.0	0.0	34.0		
51000-56000	3.5N	19.5	0.9	17.0		
56000-61000	7.5	20.5	2.5	13.0		
(1000-66001)	6.58	11.0	5.08	8.5		
66000-6933	6.0	2.5	4.0	1.5		

TABLE V RAWINSONDE-NEASURED WIND DATA NIKE-HYDAC STV, SR-076

STATICA /	11006	3989.0	3989.0 FEE! MSL
10 UCT. 68		0330	HRS MDT
ASCENSION NO.		873	

SIGNIFICANT LEVEL DATA 0658003903 WHITE SANDS SITE TABLE VI

WSTM SITE CUURDINATES E 488,580 FEET N 185,045 FEET

REL. HUM. PERCENT		•	•	•	•		•	•	•		•		•	•	•	¥ * 0−		** • 0-	** • 0-	** · O-	** •0-	** •0-	** •0-	+* ·0-	** • 0-	** 0-	** ·0-	** •0-	** • 0
E RATURE DEWPUINT	307 LN	•	•	•	•	8.0		•	່.	19.	16.	22.	•	£2.	5.5	°	• 0		å	•	•	•	•	•	•	•	•	•	• 0
FEMP	¥	2	4		2	•	~	•	•	•	•	i.	ф.	29°	38.	52.	64.	67.	-73.2	72.	71.	72.	73.	62.	50.50	54.	2	ئ د د	47.
GEUMETREC ALTITUDE	SL FEE	989,	450°	719.	562.	430°	290.	2227,	3221.	3517.	3903.	8516°	4822.	9581.	2901.	8812.	4873.	7796.	50819.5	3403.	4353°	6621.	7740.	3138.	5643.	1121.	3191.	7531.	6031.
PKESSUR	MILLIBARS	82.0	68	29.	Ç,	790	55	53.0	29.0	22.0	13.0	14.0	0000	28.0	84°C	17.0	62.0	40.0	120.0	0.50	00.00	0.5	4.0	4.0	5.0	7.0	4.5	0.0	3°2

RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS. **4**

STATION ALTITUDE 3989.0 FEET MSL 10 OCI. 68 0330 HRS MDT ASCENSION NJ. 823

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

THE PARTY OF THE P

5	
E	1
2	3
F	ì

INDEX OF REFRACTION	000	.00027	.00026	.00025	.00024	.00024	.00023	.00023	.00022	.00022	.00022	.00021	.00021	.00020	.00020	.00020	.00020	.00018	.00018	.0000	.00017	00017	.00016	.00016	.00016	.00015	.00015
ATA SPEED KNOTS	50.0	• •	ŝ	9 •	÷	ċ	c	ô	ő	<u>.</u>	ູ້	ŝ	e	4.	S.	9	ထံ	6	o	ċ	ċ	÷	÷	<u>٠</u>	ċ	'n	'n
WIND DA DIRECTION DEGREES(TN)	210.0	85.	72.	60. 61.	66.	78.	88	95	04.	12.	13.	15.	17.	21.	25.	31.	37.	40.	£3.	455.	45.	46.	44.	43.	43 °	42.	41.
PEED OF SOUND KNOTS	659.1	. 09 60 90	58.	0	58	57.	58.	58.	57.	56.	54.	53.	51.	50.	49.	47.	45.	450	46.	452.	44.	43.	42.	41.	40.	39.	38.
DENSITY S GM/CUBIC METER	1073.3	047.	016.	96.	55	50.	29.	12.	•66	86.	73.	61.	.64	37.	25.	14.	04.	89.	71.	59.	•	35.	23.	12.	00	89.	78.
REL.HUM. PERCENT	67.0	2:	-	• (, «	ô	•	.	¢	7	8	6	•	2	'n	ŝ		2	ų.	'n	m.	6	w.	w.	'n	'n	ຕໍ
TEMPERATURE S DEMPOINT SES CENTIGRADE	6.3	0 0			•	•	۰		-0.3	5 • 0 -	-1.6	۰	-3.1	۰	G	•	_5°5			-17.4	æ	-18.7	6	0	0	0	70
TEMP AIR DEGREES	12,2	ี้ ส	2	40	1 , -1	ô	÷	2	Ļ	۰			0		۰	0	0							0	-2.6	9	•
PRESSURE MILLIBARS	882.6	56.	35.	20%	9.76	77.	63.	49.	35.	22°	08,	95°	83.	70.	58.	46°	34.	22.	10.	96	87.	76.	65.	SS	44.	34.	240
GEOMETRIC ALIITUDE MSL FEET	∞ \supset	4500•0 5000•0	500°	000	000	500	.000	500.	0.0006	500	0000	0500	11000.0	1 500	2000	2500	3000	~	4000	4500°	50003	5500.	6000	6500°	7000.	7500	8000

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0330 HRS MDT ASCENSIUN NJ. 823

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COURDINATES E 488,580 FEET N 185,045 FEET

TABLE VII (Cont)

INDEX OF REFRACTION	.00015	.00015	.00014	.00014	.00014	.00014	.00013	.00013	.00013	,00013	.00013	.00012	.00012	,00012	.00012	.00011	.00011	.0001	.00011	.00011	.00010	.00010	.00010	.00010	.00010	.00010	•00000	60000	6000G*	60000
TA SPEEU KNOTS	40	4	4	*	Š	ŝ	9	ŝ	ŝ	ហ	ហ្វ	ຜ	s,	ŝ	\$		2	ж	6	;	რ	÷	Ġ.	7	. • ω	8	œ	8	6	3
WIND DA DIRECTION DEGREES(TN)	40.	€0.	40,	40.	41.	40.	40.	39°	38	37.	37.	38.	38.	40.	41.	43.	45.	47.	49.	50.	52.	52.	53.	53.	54.	54.	54.	54.	58.	55.
SPEED JE SOUND KNUTS	37.	36.	35 °	33.	32.	31.	29.	28.	27.	25	24.	25.	21.	20.	18.	17.	16.	14.	13.	12.	10.	60	08	90	04.	03.	01.	.66	97.	96
DENSITY SGM/CUBIC METER	68°	57°	47.	37.	270	17.	90	98°	89.	80.	71.	62°	54°	45°	36.	27°	19.	10.	62.	94.	85.	78.	70.	62.	55.	48.	41.	34.	27.	20.
REL.HUM. PERCENT	4.	4	4.	ŝ	ŝ	ģ	•	÷	-	-	æ	œ	ဆီ	6	œ	8	8	ဆီ	8	&	œ	æ	&	œ	æ	6	6	•	•	•
ERATURE DEWPOINT CENTIGRADE	25°	23,	40	4,	ູ່ດ	9	2	ဆိ	29°	29°	30°	ď	2	ကိ	4	ហំ	ŷ	7°	ŝ	6	ဝံ	-	•	•	•	•	•		•	
TEMP AIR UEGREES	¢	0	9	0	•	ô	ĭ	2°	*	Š	ů	7.	å	ô	0	ů	2	ů	ເດ	ŝ	-	8	6	ċ	?	'n	4°	÷		8
PRESSURE MILLIBAKS	14.	0.40	940	84°	750	65°	560	47.	38°	30°	21°	13,	05.	97°	88°	80.	73.	65°	57°	50.	43.	36.	. 62	22.	15.	. 80	0).	95°	89.	82.
GEOMETAIC ALTITUDE MSL FEET	8500.	9000	9500°	0000	0500.	10000	1500°	20002	2500°	3000.	3500°	40005	4500.	5000.	5500°	6000	e500°	70007	7500.	8000°	8500.	9000°	9500.	.0000	.0050	1,000.	1 500.	2000.	2500.	30000
	ETAIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX FUDE AIR DEWPOINT PERCENT GM/CUBIC SOUND DIRECTION SPEED OF FEET MILLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTI	ETAIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX FUDE FUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF FEET MILLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 688.0 637.8 240.5 24.3 1.00015	ETAIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF FET MILLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 668.0 637.8 240.5 24.3 1.00015 000.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.3 24.5 1.00015	ETAIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF FET MILLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 668.0 637.8 240.5 24.3 1.00015 500.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.3 24.5 1.00015 500.0 494.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014	FIRIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF OF THE CONTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 687.8 240.5 24.3 1.00015 500.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.5 24.7 1.00015 500.0 494.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014 1.00014	FIRE PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX OF TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF OF THE CONTIGRADE FET MILLIBARS DEGREES CENTIGRADE FET MILLIBARS DEGREES CENTIGRADE FOR METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 657.6 635.4 240.5 24.3 1.00015 500.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.5 24.7 1.00014 500.0 494.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014 500.0 484.6 -8.4 -24.9 25.2 637.3 633.7 240.9 24.9 1.00014 500.0 475.0 -9.5 -25.7 25.6 1.00014	FIRE PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX TUDE AIR DEMPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF OFFICE STORMS DEGREES CENTIGRADE FET MILLIBARS DEGREES CENTIGRADE FOR METER KNUTS DEGREES TN) KNOTS REFRACTION 500.0 504.2 -5.1 -22.6 24.0 657.6 635.4 240.5 24.3 1.00015 500.0 494.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014 500.0 484.6 -8.4 -24.9 25.2 637.3 633.7 240.9 24.9 1.00014 500.0 475.0 -9.5 -25.7 25.6 527.4 632.4 241.1 25.6 1.00014 500.0 465.7 -10.7 -26.5 26.0 617.7 631.0 240.9 26.1 1.00014	FIRE PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF OFFICE SUUND DIRECTION SPEED OFFICE SUUND SPEED OFFICE SUUND DIRECTION SPEED OFFICE SUUND DIRECTION SPEED OFFICE SUUND SPEED OFFICE S	FTALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA INDEX CLUBE ALR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SUU.0 514.3 -5.1 -22.6 24.0 687.8 240.5 24.7 1.00015 1000.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.6 24.7 1.00016 1000.0 694.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00014 1.00018 1.00018 1.00019 1.000.0 445.5 -11.8 -22.8 26.4 598.8 628.3 239.3 226.4 1.00013	FTALC PRESSURE TEMPERATURE REL-HUM, DENSITY SPEED JF WIND DATA OF TUDE ALR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SUUND BETALLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION 500.0 514.3 -5.1 -22.6 24.0 687.6 636.4 240.5 24.7 1.00015 500.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.6 24.7 1.00016 500.0 494.3 -7.3 -24.1 24.8 647.4 635.1 240.6 24.7 1.00014 500.0 484.6 -8.4 -24.9 25.2 637.3 633.7 240.9 24.9 1.00014 500.0 475.0 -9.5 -25.7 25.6 627.4 632.4 241.1 25.6 1.00014 500.0 456.5 -11.8 -27.3 26.4 608.2 629.7 240.4 26.4 1.00013 500.0 447.5 -12.9 -28.2 26.8 598.8 628.3 239.3 26.4 1.00013 500.0 447.5 -12.9 -29.0 27.2 589.5 627.0 238.0 26.3 1.00013	FIRESURE TEMPERATURE REL.HUM, DENSITY SPEED JF WIND DATA INDEX INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF GET ALLIBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION SUUND SI4.35.122.6 24.0 637.8 240.5 24.3 1.00015 200.0 504.2 -6.2 -23.4 24.4 657.6 636.4 240.9 24.7 1.00015 200.0 494.37.324.1 24.8 657.6 636.4 240.9 24.7 1.00015 200.0 445.0 -9.525.7 25.2 637.3 633.7 240.9 24.9 1.00014 200.0 445.0 -9.525.7 25.6 1.00014 200.0 445.512.9 -28.2 26.4 601.2 629.7 240.9 26.1 1.00013 200.0 447.512.9 -28.2 26.8 599.8 628.3 239.3 26.4 1.00013 200.0 438.714.029.8 27.2 580.5 625.6 237.9 237.9 25.9 1.00013 200.0 438.715.129.8 27.6 580.5 625.6 237.9 257.9 1.00013	FIRE PRESSURE TEMPERATURE REL-HUM, DENSITY SPEED JF WIND DATA INDEX INDEX LINDE ALR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF GM/CUBIC SUUND SITURE SERVE SUUND SITURE SERVE SUUND SITURE SERVE SUUND SITURE	FTAIC PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX INDEX TUDE AIR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SILONE STAND DIRECTION SPEED OF SILONE STAND SPEED OF SILONE SPEED OF SPEED OF SILONE SPEED OF SPEED OF SILONE SPEED OF	FIRE PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX INDEX DEGREES CENTIGRADE METER KNUTS DEGREES(TN) SPEED OF SPEED OF SULD DIRECTION	FIRE PRESSURE TEMPERATURE REL.HUM. DENSITY SPEED JF WIND DATA INDEX INDEX USER SCENTIGRADE REL.HUM. DENSITY SPEED JF WIND DATA OF TWO SPEED JF WILLIBARS DEGREES CENTIGRADE RETER KNUTS DEGREES (TN) KNOTS REFRACTION SPEED JF WHO SOLITS AND SPEED JF WILLIBARS DEGREES CENTIGRADE REFRACTION SPEED JF WHO SOLITS AND SOLITS A	FIRE PRESSURE TEMPERATURE REL-HUM, DENSITY SPEED JF WIND DATA INDEX LINE ALR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SUND DIRECTION SPEED O	FTALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA INDEX LIDEA DENSITY SPEED JF WIND DATA INDEX LIDEA DEMPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SUCCESSION SPEED SPEED JF SPEED JF SUCCESSION SPEED SPEED JF SUCCESSION SPEED SPEED JF SUCCESSION SPE	FIALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA INDEX INDEX LIBBARS DEGREES CENTIGRADE METER KNUTS DEGREES(TN) SPEED OF MOTES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION SPEED OF MOTES CENTIGRADE METER KNUTS DEGREES(TN) KNOTS REFRACTION SCOOL SOUR SOUR SOUR SOUR SOUR SOUR SOUR SOUR	FILL PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JR WIND DATA INDEX INDEX LUBER ALR DEWPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF MATER NULL BARS DEGREES CONTIGRADE CANTIGRADE METER NULLS DEGREES CTN) KNOTS REFRACTION SOUR SOUR SOUR SOUR SOUR SOUR SOUR SOUR	FIREC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA INDEX INDEX LUBER LIBRAS DEGREES CENTIGRADE METER RNUTS DEGREES(TIN) RNUTS REFRACTION SPEED OF SOUR SOUR SOUR SOUR SOUR SOUR SOUR SOUR	FILLIBARS DUGREES CENTIGRADE AIR DEMPDINI PERCENT GM/CUBIC SUUND DIRECTION SPEED OF MIND DATA NEED OF	FILL PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA ALR DEMPORNT PERCENT GM/CUBIC SUUND DIRECTION SPEED GREES CENTIGRADE METER KNUTS SPEED JF MIND DATA NOTES SPEED GREES CENTIGRADE METER KNUTS SPEED JF MIND DATA NOTES SPEED GREES CENTIGRADE METER KNUTS SPEED JF MIND DATA NOTES SPEED JF MIND MATER KNUTS SPEED JF MIND MATER NOTES SPEED JF MIND MATER NO	FIALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA ALK DEMPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED OF SPEED JF ALLIBAKS DEGREES CENTIGRADE METER KNUTS DEGREES(TION SPEED OF SPE	FIALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF MIND DATA ALL INDEX LUJUE ALR DEMPOINT PERCENT GM/CUBIC SUUND DIRECTION SPEED GF CONTIGNABLE SCENTIGRADE NUTS SPEED SPEED CONTIGNABLE SCENTIGRADE NUTS SPEED SPEED CONTIGNATION SPEED SPEED CONTIGNABLE SCENTIGRADE NUTS SPEED SPEED SPEED CONTIGNATION SPEED	FILL PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA ALK DERRETURE SECUND OINGERESTION SPEED OF CHILDRAKS DEGREES CENTIGRADE NOT SECUND OINGERESTION SPEED OF CHILDRAKS DEGREES CENTIGRADE NOT SECUND OINGERESTION SPEED OF CHILDRAKS DEGREES CENTIGRADE NOT SECUND OINGE N	FIALC PRESSURE TEMPERATURE REL-HUM. DENSITY SPEED JF WIND DATA INDEX OFFED JEAN PROPERTY OF A CASE OF A CA	THIS PRESSURE TEMPERATURE RELIMING DENSITY SPEED JA WIND DATA DENSITY SPEED JA WIND DATA DENGES CENTIGRADE METER SCHOOL SPEED JA DENGES CENTIGRADE METER SCHOOL SPEED JA DENGES CENTIGRADE METER SCHOOL SPEED JA DENGES CENTIGRADE METER DENGE SCHOOL SPEED JA DENGE SCHOOL SPEED	FILL PRESSURE TEMPERATURE REL-HUM DENSITY SPEED JF WIND DATA INDEX DEGREES TO SERVING MIND DATA NOT BE SERVINGENT PRESENT NOT SERVING MIND DATA NOT BE SERVINGENT PRESENT NOT SERVINGENT N	TALLE PRESSURE TEMPERATURE REL.HUM, DENSITY SPEED JF WIND DATA OF MEDIN SPEED OF WENDON TO SPEED JF WIND DATA WAS A SPEED JF WIND DATA OF WENDON TO SPEED JF WIND DATA WAS A SPEED	THIC PRESSURE TEMPERATURE REL-HUM DENSITY SPEED JF WIND DATA INDEX NOTES TALL IBAKS DIEGRES CORPORATE TO CHICOLD STOUND

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 (330 HRS MDT ASCENSION NO. 823

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE VII (Cont)

INDEX	REFRACTION	1.000092	1.000001	1,000089	1.000087	1.000086	1.000084
T A SPEED		44.4	46.4	48.7	53.0	53 ° 1	56.2
WIND DATA		256.4	257.1	256.8	256.6	256.4	256°5
SPEED OF	KNOTS	594.6	593.2	591.7	590.2	588.8	Ø
DENSITY	METER	412.9	405.6	398.5	391.4	384.5	377cB
REL.HL		27.9**	25.2**	22.6**	20.0**	17.4**	14.8**
ERATURE REL.HUM.		-51°7 27.9**	25.	22.	-57°4 20°0**	17.	-61°7 14.8**
TEMPERATURE RELOHL			25.	22.		17.	
EMPERATURE DEMPOTANT	ES CENTIGRADE	276.4 -40.0 -51.7	-53.5 25.	-42.3 -55.4 22.	-43.457.4	-44.5 -59.5 17.	-45.7 -61.7

	.0000	.00008	.00008	•0000°	.0000	.0000	.0000°	.00000	.0000	.0000	.0000°	.00007	.00006	1.000067	.00006	00000	•00000	•00000	•00000	.00006	.0000	.0000	.00000	.0000°	.0000	.0000	
•	'n	ŝ	æ	9	1.	å	•	2	۲	2	~	å	ŝ	55.0	2	0	ô	•	9°	ô	-	40	0	6.	ι,	ຜູ	
,	56°	56°	55.	55°	55.	55.	55°	56.	56.	57.	58	58.	59.	260.1	60°	60°	59.	58°	58.	57.	សូ	53.	54.	54.	54.	ຜ	
	88	87.	85.	84.	82°	81.	79.	78°	77.	75.	74.	73.	71.	570.4	. 69	67.	66.	65.	63.	62.	61.	61.	60.	60.	59.	58.	
	84.	172	71°	54.	58°	52.	45.	39.	33.	26.	20.	14.	00.	302.1	•96	90.	85.	.61	74.	58.	52.	56.	51.	Ę5	39.	34.	
	17.4**	14.8**	12.1**			m	9	.,	** *0-	** 0-	** *0-	** °0-	-0° **	+* "0-		** *0-	+* *0-	** *0-	** *0	** *O-	** *0-	+* *0-	** "0-	** *0-	+* 0-	***0-	
	9.5 17.	1.7.1	4-1	.8 9.	6°9 0°0	4-1 4-3	1.0 1.6	0-	. 0-		•	•	٥		•0-	•	•	•	•	•	•	•	•	•	•	•	
	4.5 -59.5 17.	•7 -61°7 1	-8 -64-1	8.0 -66.8 9.	9.1 -70.0 6.9	0.2 -74.1 4.3	1.4 -81.0 1.6	2.5 00.	a.s 00.	4.5	5.5	6.5	7.6 0.	-0-	9.6 00.	0.0	1.6 0.	2.6 0.	3.6 0.	4-5	5.0	5.4 0.	5.8 0.	6.3 O.	6.7 0.	7.4 0.	
	52.3 -44.5 -59.5 17.	46.6 -45.7 -61.7 1	41.1 -46.8 -64.1	35.7 -48.0 -66.8 9.	30.4 -49.1 -70.0 6.9	25.2 -50.2 -74.1 4.3	20.1 -51.4 -81.0 1.6	15.1 -52.5 00.	09.9 -53.5 00.0	04.9 -54.5 0.	00.0 -55.5 0.	95.3 -56.5 0.	90.6 -57.6 0.	1 -58.6 00.	81.6 -59.6 00.	77.3 -60.6 0.	73.1 -61.6 0.	69.0 -62.6 0.	64.9 -63.6 0.	61.0 -64.5 0.	57.0 -65.0 0.	53.1 -65.4 0.	49.4 -65.8 0.	45.7 -66.3 0.	42.1 -66.7 0.	38.6 -67.4 No.	

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. **#**

FEET MSL	HRS MDT	
3989,0 FI	0330 HR	
		α 4,7
ALT ITUDE	80	1 2 N
STATION	10 OCT.	ASCHUSTIN ALL

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE CUURDINATES E 488,580 FEET N 185,045 FEET

					TABLE VII	(Cont)				
GEUMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERAT AIR DEW UEGREES CENT	FRATURE DEWPOINT SENTIGRADE	Re L. HUM. Percent	DENSITY GM/CUBIC METER	SPEED UF SOUND KNUTS	WINU DAT DIRECTION DEGREESTIN)	TA SPEFO KNOTS	INDEX OF REFRACTIUN	
	55.0	r) e	ဝ		29°	57,	ક જ	4	,0000	
9000	31.	69	-	*	25°	55	56,	il.	.00005	
49500.0	128.4	-70.5	•	** °O-	220°7	554.3	257.3	43.5	1,000049	
0000	25.	, T	ဝိ	*	16,	52	59.	ۍ.	\$0000 *	
3500.	220	2	၁	•	11.	51.	δ υ o	~	.0000	
•	ž	ů	ຳວ		07.	50.	52 °	7 °	+00000+	
1500.	5.	ૡ૾	0°	*	01.	50.	63.	7.	.000C	
20002	2°	°	°0	≯	96.	51.	64.	\$	*0000	
2500.	=	2	· 0	# •	91°	51.	65,	÷	.0000	
3000.	~	ငိ	ဝံ	*	86.	51.	66.	~	40000°	
3500°	4	2	•	*	81.	51.	67.	ش	40000	
4000.			ာံ	-O. **	76.	52.	689	٠,	.00003	
4500.	6	÷	• o	*	71.	53.	69	<u>.</u>	.00003	
50000	ç,	بـ	• •	*	67.	ж Ю	• 69	-	.0000	
55500.	•	-	• •		63.	52,	€8.	6	.0000	
6000 .	7	ř	•	*	59°	52.	77.	ô	.0000	
o 500°	c	5	•°	*	50.0	52.	750	ф	.0000	
7000.	7.	72°	•		51.	51.	79.	6.	.0000	
7500.	•	73.	°0	#	48.	50.	83.	\$.00003	
8000.	·	å	• •	*	44.	50.	87.	3.	.0000	
8500°	္	ن	• •	*	40,	52.	89.	ŝ	.00000	
9000.	ж •	0	ပိ	*	35.	53.	92.	2	.00003	
~0056	Ġ	ŝ	•	¥	31.	ა	97.	ф •	.0000	
0000	'n	ဆိ	•	*	27.	56.	04.	;	.0000	
0500.	4	7.	°	*	23.	58	1.1.	:	.0000	
10001	۲,	Ġ	•	•	20.	50	16.	~	.0000	
1500.	6	ů	·	*	16.	61.	20.	ŝ	.0000	
.000	7.	4,	•	*	13.	ۍ د کې	16.	4.	.0000	
2500.	9	ë	•	•	.60	64.	11.	ູ່	.0000	
63000.0	4 0	5	•	** ·()-	06.	65.	98.	•	.00002	

AT LEAST UNE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. *

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0330 HRS MDT-ASCENSION NO. 823

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE VIT (Cont)

INO EX	REFRACTION	.0000	.0000	,0000	.0000	.0000	.00002	.0000	.00001	,00001	.0000	.00001	1.000017	.00001	.0000	.00001	.00001	.00001	0000	.0000	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001
TA SPEE	KNOTS	•	•		۰		o	Э	ء 	å	ผู้	Š	12.0		•	c	•	•		c	•	9	•		•	•	•	•	•	•	6
WIND	S.	77,	57.	44.	31.	29°	e e	35.	33.	32°	32,	32°	232.8	31.°	29.	66°	16.	59°	20.	0	å	56.	12.	87.	62.	53.	58.	62.	65.	67°	10
SPEED OF	KNOTS	. 99	66.	999	67.	67.	67.	6 В•	68°	899	69.	. 69	569.7	70.	70.	70.	71.	71.	71.	72.	72.	72.	73.	73.	73.	74.	740	74.	74.	74.	74.
DENSITY S	ETER	03 .	7	ထိ	6.	ъ.	4	6	ş	4	ç N	ô	78.5	ę,	٤	ŝ	7°	6	2	ທີ	÷	٠ د	Ξ.	6	8	ç	S.	'n	2	-	•
C 5																															
		# #	*	*	*	*	*	* *	*	*	*	¥ *	* *	* *	* *	* *	*	*	*	* *	*	¥	* *	* *	* *	* *	*	* *	*	*	*
		+* *0-	** •0-	** *0-	•	** •0=	•	•		•	•	•	** °0-	•	•	*	•				** *0-	•	** *0-	•			•	•	** *0-	** "0-	** *0-
E REL.HUM.	DE	!	i	1	•0-	1	•0-	-0-	· n-	• 0 -	-0-	•0-	ô	°0-	0-	* 0	•0-	0-	•0-	•0-	• 0 -	. •0-	0 -	0-	.0-	0-	• 0 -	.0-	0-	0-	•
EMPERATURE REL.HUM. DEWPOINT PERCENT	EES CENTIGRADE	.8	• 0 9• ·	۰۵ ۳۰	.1 00.	00	.0 0.	0.3 00.	0.1 00.	9°8 0° -0•	0- 0- 9-6	9•3 0° -0•	°0-	8.8 00.	8.6 00.	8°4 0° -0° *	8.1 00.	7.9 00.	7.6 00.	7.4 00.	7.1 00.	6.9 00.	6.6 . 00.	6.4 00.	6.1 00.	5.9 00.	5.7 00.	5.6 00.	5.5 00	.0 0-	5.2 0
TEMPERATURE REL.HUM. R DEWPOINT PERCENT	EES CENTIGRADE	.9 -61.8 0.	.4 -61.6 0	.9 -61.3 0	.5 -61.1 00.	.1 -60.8 0.	°1 -60°6 0° -0°	.460.3 00.	.1 -60.1 0U.	.9 -59.8 00.	.659.6 00.	.4 -59.3 O0.	2 -59.1 00.	•1 -58°8 0° -0°	.0 -58.6 00.	*6 -58°4 0° -0° *	.8 -58.1 OO.	.7 -57.9 00.	o7 -57.6 00.	°7 -57.4 00.	.8 -57.1 00.	.856.9 0	.956.6 . 00.	•0 -56°4 0° -0•	ol56.1 00.	.2 -55.9 O0.	.4 -55.7 00.	.6 -55.6 O0.	.8 -55.5 OO	.1 -55.4 00	.3 -55.2 0

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. ₩ ₩

i

:

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0330 ORS MDT ASCENSION NO. 823

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE VII (Cont)

INDEX	10	REFRACTION
ITA	SPEEU	> KNOTS
WIND DATA	DIRECTION SPEED	DEGREES (TN)
SPEEU UF	SUUND	KNUTS
RFL, HUM. DENSITY SPEED UF	NT PERCENT GM/CUBIC	METER
RFL, HUM.	PERCENT	
	_	
	DEWPUINT	CEN FIGRADE
TEMPERATURE	۲	DEGREES CENTIGRADE
	DEWPUINT	MSL FEET MILLIBAKS DEGREES CENTICKADE

.00001	,0000,	.00000	.00001	.0000	.00001	.00000	000000	00000"	000000	000000	.00000	.00000	.00000	.00000	• 00000	00000	00000	00000	000000	.00000	000000	• 000000	00000	• 000000	00000.	• 00000	00000	1.000006	• 00000
5	•	0	۰	9		c	c	•	œ	10,8	ຸດ	n	e M	•	'n	ວໍ	2	4	ທ	s N	4.	4.	9	2			•		
58.	51.	42°	33.	ວໍ	07°	92.	œ &	ŝ	'n	83,3		<u>;</u>	٠ ش	ທໍ	97.	6	14.	10.	07.	03.	æ	Š	3	•	9	•	16.		
74.	75°	75.	75.	75.	5€.	76.	77.	78.	78.	79.	78.	78.	78.	78.	78.	78.	78.	77.	78.	78.	79.	79.	80.	80.	80.	81.	81.	582.2	82.
80	2°	Ś	Š	4	S	2,	۲,	ဝံ	3	8	^	9	ŝ	+	3	3	2	;	•	•	6	ъ Ф	8		•	•	5	24.8	4
										*							*	*	*	* *		¥	*	*	* *	* *	* *	*	* *
0-	-0	01	-0-	0-	°0-	-0	0-	°0-		-0-		0	0						O		0,	0	-0	-0-	0	0	-0-	-0-	0
0°	၁ီ	°o	ဝ	ဘီ	ລໍ	ဝိ	°O	°O		°		•	o	•	°			•	•	•	°	0	o	•	•	•	•	•	°o
ເດ	ທີ	54.	4	54.	9	4。	u) o	2°	å	ç	2	င္ပံ	2	2°	٠	2	52.	2	2	2	7	7	4	0	÷	0	6	9.64-	6
ိ	ŝ	ô	8	7 °	7	Ŷ	S	ιυ °	4	4.	'n	w	ů	Ö	٦,	ĭ	°	Ċ	6	6	&	ဆံ	~	~	7	6.	9	15.9	٠ د
8500.	9000.	9500°	0000	0500.	1000.	1500.	2000.	2500°	3000.	3500.	4000	4500.	85000	85500°	600U.	65000	7000	7500.	8000.	8500.	9000	9500.	0000	0500.	1000.	1500.	2000.	92500.0	3000.
													1	3															

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

3989.0 FEET MSL	0330 HRS MDI	823
ALT ITUDE 3989.0	68	
STATION	10 OCT.	ASCENSION NO.

UPPER AIR DATA 0658003903 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

	7	j
۰	1007	
	,	2
	2	١
	VTT	1
	TARTE	
	2	3
	Ē	ì

INDEX OF REFRACTION	1.000005	1.000005
TA SPEED KNOTS		
WIND DATA DIRECTION SI DEGREES(TN) KI		
SPEED OF SCUND KNOTS	583.1	787 784 584 564 564 664 764 764 764 764 764 764 764 764 7
DENSITY GM/CUBIC METER	23 23 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	21.9 21.4 20.8
REL.HUM. Percent	* * # * * *	* * * *
TEMPERATURE R DEWPOINT EES CENTIGRADE	000	0000
TEMP AIR DEGREES	148.9	477
PRESSURE TEM AIR MILLIBARS DEGREES	144 24 5	499
GEOMETRIC ALTITUDE MSL FEET	93500.0 94000.0	95000.0 95500.0 96000.0

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATIUM ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0330 HRS MDT ASLENSION NJ. 823

MANDATURY LEVELS 0658003903 WHITE SANDS SITE

WSTM SITE COURDINATES E 488,580 FEET N 185,045 FEET

TABLE VIII

WIND DATA		7	0 21.	3	13	9 16.	2 20.	6 22.	24.	6 26.	6 26.	0 31.	386	3 55.	3 57.	1 50.	0 51.	1 45.	2 32.	6 16.	2 16.	•6	7 12.	9 2.	9 3.	2 8.	14.	
2	DEGR	8	•	σ	214	2	*	*	4	33	3	ເດ	S	S	S	ð	n	S	3	6	-	4	ന	40	152	\mathfrak{D}	110	
REL.HUM.		62.	53.	44.	49.	55.	23.	24.	25.	27.	29.	28.	30.	*	**°0-	***0-		***0-	***0-	**°0-	***0-	***0-	*	***0-	•	***0-	***0-	***0-
MPEKA TURE	CENTIGRADE	•	•		-2.1	ري. •		0		27.	32°	6	,3	•	•	•	•0			•	•0	•0	C	•	•	•	•	•
7 0	DEGREES	9	•	2	7.9	•	•	•	•	2.	6	9	35	:O	ເດ	61.	65.	4	71.	71.	•	7	59.	-	5	52.	2.	æ
GEUPUTENTIAL	FLET	22	69	46	1,0352。	234	445	674	20	187	419	800	160	568	C45	321	631	066	420	ϵ 51	114	425	758	258	859	245	716	330
PRESSURE GE	MILLIBAKS	850.0	800.0	750.0	700.0	650.0	600.0	550.0	500°C	450.0	400°0	350.0	300.0	250.0	200.0	175.0	150.0	125.0	100.0	80.0	70.0	0.09	20.0	40.0	30.0	25.0	20.0	15.0

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. *

.0 FEET MSL	30 HRS MDT	
	H 0690	A24
ALTITUDE	89	ON
STATION	10 OCT. 68	IVNUCVV

SIGNIFICANT LEVEL DATA 0668003906 WHITE SANDS SITE

MSTH SITE COURDYNATES E 488,520 FEET N 185,045 FEET

TABLE IX

PRESSUR	E GEOMETRIC	ū	IPERATURE	REL.HUM.
	9	ď	DEMPOINT	ER C
MILLIBAR	SL FEE	w	CENTIGRADE	
82.	989.	%	•	•
Ŷ	513.	4	•	•
Ø	184.	ċ	•	
74.	605.	10.9	3.2	۵
66.	891.	ň	•	
σ	0758.	•	•	•
12.	3978.		-	
602.0	14413.4	0.5	-21.8	17.0
~	5759.		1.	•
23 °	8095.		5	•
5,6	677	4	2	•
.66	1770.	-35.2	•	•
24.	8193.	ô	•	-0° **
α	2228.	6	•	** ·0-
80.	794.	6	•0	** •0-
49.	6634.	•	•	** • 0-
41°	7737.	ŝ	•	** • 0-
16.	1587.	2	•0	** ·0-
00	4491°	6	•	** ·0-
m	8138.	\$	•	** •0-
3.	3623.	2	•	** • 0-
37.0	.959	-54.9	ċ	** • 0-
2.	8065	ທໍ	•	** *0-
•	108016.3	-40.9	•	+* · 0-

RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

UPPER AIR DATA

E COORDINATES 488,580 FEET 185,045 FEET	INDEX OF REFRACTION	0027	0027	.00027	.00027	1,000266	.00026	.00025	.00025	.00024	.00024	00023	.00022	.00022	.00021	.00021	.00020	.00020	.00020	00019	.00019	.00018	.00018	.00017	.00017	.00017	.00016	-00016	.00016	.00015	.00015
WSTM SITE	TA SPEED KNOTS	•		•		7.5	•	•	•	•	•	•	•	•	7.	7.	٠ ۲	-	8		2	4	5	Š	5	E.		1.	-	-	-
	WIND DADIRECTION	00.	00	13.	26.	139.8	53.	63.	72.	75.	78.	81.	85.	90.	94.	.66	40	10.	17.	23.	28.	32.	35.	36.	37.	35.	34.	32.	20.	29.	. 62
906 SITE	SPEED OF SOUND KNOTS	58	58,	61.	60.	Ç	58°	58.	57.	57.	59°	58.	58.	57.	56.	55.	54.	53.	51.	.64	48.	46.	45.	44.	44.	43.	43.	641.9	40.	639.6	38.
0668003 WHITE SANDS TABLE X	DENSITY GM/CUBIC METER	074.	073.	047.	30.	0	98.	82.	67.	49.	26.	11.	97.	83.	.69	55.	43.	31.	20.	08.	97.	36.	75.	63.	49.	36.	23.	12.	01.	91.	80.
ż	REL.HUM. PERCENT	ļ	ဝိ	7°	7°	58.8	9.	ô	:	9°	å	•	å	10	æ	9	ŝ	ŝ	9	-	7.	æ	,	-	2	17.8	8	8	&	18.0	æ
. MSL	ERATURE GEWPOINT CENTIGRADE	4.8	•	•	•	4.9	•	•	0	•	۰	•	•	-1.7	¥	•	•	•	•	•	6	o.	;	-	<u>.</u>	•	5	2	3	-24.5	5
989,0 FEET 0630 HRS MDT	TEMP AIR Degrees	2	ŝ	ų	'n	12,7	2,	å	•	Ö	2	•	•	11.0	•	•	0	•	•	4.9	•	•	•	•	•	•	•	•	•	ا س م	•
ALTITUDE 398 68 00 10 NO. 824	PRESSURE MILLIBARS	2	2°	ç,	ô	835.5	o,	Ś	.	۰	e O	6	'n	2	6	•	9	7	φ.	•	.	'n.	• ~4 :	•	20	577.7	•	•	Š	535.1	•
STATION AL 10 OCT. 68 ASCENSION	GEOMETRIC ALTITUDE MSL FEET	989°	000	500°	000	5500.0	.000	500.	000	500°	000	500.	000	9500.	.0000	10500.	1000	1500.	2000.	500°	3000	3500.	4000.	4500.	5000	5500	e 0009	6500.	7000.	7500.	8000

STATION ALTITUDE 3989.0 FEET MSL 10 DCT. 68 0630 HRS NDT ASCENSION NO. 824

UPPER AIR DATA 0668008906 White Sands Site

WSTM SITE COORDINATES E 488+580 FEET N 185+045 FEET

TABLE X (Cont)

INDBX OF REFRACTION	1.000153	·1000.	.00014	\$1000·	.00014	# COOO !	96	61000	.00012	.00012	.00012	.00012	.00012	.00011	.00011	.00011	.00011	.00011	000010	.00010	.00010	.00010	.00010	01000	\$0000°	00000	.0000	•0000
ATA SPERO KNOTS	21.0	-	ં	٠ ج			- c	, _,	6	ö	_		~	.	3	e,	ġ	-	.	<u>.</u>	~	~	-	-	~	CG.	· N	•
WIND DA DIRECTION DEGREES(TN)	231.6 233.5	93	တ	0	က က		• · · · · · · · · · · · · · · · · · · ·	, ca	0	37.	37.	36.	63 63	200	8 8	36.	37.	δó.	42.	43.	43.	55	46.	430	43.	444	Ę.	46.
SPEED OF SOUND KNOTS	683 688.9	34.	60	M	3	6.0		26-	4	8	22.	20.	19.	10.	17.	<u>.</u>	14.	13.	-	60	000	06.	÷	680	50	00	90.	97.
DENSITY GM/CUBIC HETER	689.6	40.	E .	24	17.	200	• • • • •	200	69	9	31.	43.	34.	26.	17.	90	50	93	ه د د	77.	2	63.	8 8	48.	41.	34.	26.	10.
REL.HUM. PERCENT	18.0	8	E	.	.	.	s c	9 0	9	Ö	.	8	.	.	.	ë	.	.	ъ.	ċ	ö	ċ	_;	ä	સં	ċ	.	
ERATURE DEWPOINT CENTIGRADE	-26.2	2.7.	80	500	30		9 6 9 6) (a)	4	8 53	36.	37	90	39.	6	90	41.	\$2	₽ 3	•	ຄ	ຕ	ġ		8	49	•	ы •
TEMP AIR Degrees	ນ ລ ຄູ	÷	ස	Ġ.	o.		• •	, 4.	15.	÷	17.	18.	19.	21.	તં	en ev	\$2	23.	26.	-	Ş	ö		ค	÷	S. S.	•	8
PRESSURE MILLIBARS	514. 504.	94.	9	. d.	ر د د		• c	200	21.	12.	9	96	. ສ	့	330	653	8 0	51.	ė.	36.	29.	22.	15	60	.20	93.	89.	82.
METRIC ITUDE FEET	0.00	90	00	8	00	000			00	00	80	90	00	99	8	00	90	80	90	90	00	80	8	80	80	80	500.	00

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0630 HRS NDT ASCENSION NO. 824

UPPER AIR DATA 0668003906 WHITE SANDS SITE

WSTM SITE COORDINATES E ABB, SBO PRET N 185,045 FRET

TABLE X (Cont)

INDEX	<u>د</u>	REPRACTION
T.	SPERO	X NOT S
MIND DATA	01 ABCT 10N	0668ES (12)
SPEED OF	SOUND	KNOTS
DENSITY	GM/CUBIC SOUND	K E E E E E E E E E E E E E E E E E E E
REL.HUM.	PERCENT	
TEMPERA TURE	DEWPOINT	CENTIGRADE
TEMP	AIR	DEGREES
PRESSURE		MILLIBARS DEGREES CENTIGRAU
GEOMETRIC	ALTITUDE	MSL FEET

X 20 20 20 20 20 20 20 20 20 20 20 20 20	REPRACTION	00000	.00000	.0000 B	.0000	.0000	.0000	.0000	.0000B	00000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	0000.	•0000•	•0000	90000	.0000	90000	.0000s	.0000	.0000s	. 0000 s		ရ (၁)
TA SPER	KNOTS	47.3	•	-	ੌ ਜੀ	:			ó	•	•	ċ	-	ċ	ċ	-	÷	2	•	6		•	÷	63	2	÷	:	2	S,	51.6	6
MIND DA	S (40.	47.	49.	3.	50.	30.	50.	50,	<u>5</u> 1°	52.	5 5	ಕು ಬ	5.	, S	53.	200	51.	5 5 5	ಜ್ಯ	я ЭЭ•	54.	56.	5.5	• ເດ ະຄ	53	53.	54.	54.	255.2	55.
P G G U	Z	95.	946	92.	91.	99.	900	86.	82	84.	82.	81.	79.	77.	76.	740	73.	71.	70.	.69	69	67.	66.	65.	64.	62.	61.	60.	60	560.6	60.
DENSITY S	RETER	1.1.	š	97.	90°	83 •	77.	0,	64.	ည ထ	51.	<u>ئ</u> ئ	39.	33.	26.	21.	15.	.60	03.	97.	90.	84.	79,	73.	68.	62.	57.	52.	46.	239.9	34.
ř.		u	_	*	×	*	*	*	¥	*	¥							¥	*	* *	*	¥	*	₩	*	¥	*	*	¥	¥	¥
REL.HUM FORCENT		δ. 8	٠. ٥	3.2	, de	9 • 6	ç	7.	¥ CO	, S	7 .	•	•	•	•	ô	ဝံ	•	•	ဝိ	•	•	•	*	*	*	*	*	* 0-	** •0-	* 0
ERATURE REL.H DEWPOINT PERCE	TIGRADE	5.1 16.8	57.0 15.0	59.0 13.2	61.0 11.4	.3 9.6	65.7 7.9	68.4 6.1	1.7 4.34	76.1 2,54	4.0 0.7	.01	•0-	•0-	•0•	•0-	0-	• 0	0-	°0-	-0-	-0-	•0-	* •01	* 01	* • 0 -	* °01	* 0-	* •0-	0	
TEMPERATURE KEL.H	ES CENTIGRADE	9.1 -55.1 16.8	0.3 -57.0 15.0	1.4 -59.0 13.2	2.5 -61.0 11.4	3.7 -63.3 9.6	4.8 -65.7 7.9	6.0 -68.4 6.1	.1 -71.7 4.3*	8.2 -76.1 2.5*	9.4 -84.6 0.7	0.5	10.7 00.	2.8 00.	4°0 0°	5.2 00.	6.3 00.	7.5 00.	8.7 00.	9.2 00.	.0- 0.	0.5	1.4 00.	2.3 00. *	3.2 0. 10. *	4.1 00. *	*·0 0. 0.0	* 0- 00 0.9	6.1 00. *	0 0 6	66.2 0
TEMPERATURE KEL.H	EGREES CENTIGRADE	76.6 -39.1 -55.1 16.8	70.5 -40.3 -57.0 15.0	64.5 -41.4 -59.0 13.2	58.6 -42.5 -61.0 ll.4	2.8 -43.7 -63.3 9.6	47,2 -44.8 -65.7 7.9	41.7 -46.0 -68.4 6.1	30.3 -47.1 -71.7 4.34	31.1 -48.2 -76.1 2.5*	26.0 -49.4 -84.6 0.7	20.8 -50.5 00.	15.6 -51.7 00.	10.5 -52.8 00.	05.6 -54.0 00.	00.8 -55.2 00.	96.1 -56.3 00.	91.5 -57.5 00.	87.0 -58.7 00.	82.6 -59.2 00.	78.2 -59.6 00.	73.9 -60.5 00.	69.6 -61.4 00.	65.5 -62.3 0° -0° *	61.5 -63.2 00. *	57.6 -64.1 00. *	53.7 -65.0 00. *	¥ 0- 0.0 -0.05	46.3 -66.1 00. *	42.7 -65.9 00	9.1 -66.2 0

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. *

FEET MSL	HRS MDT	
	Ξ	
3989.0	0630	
8		824
ALTITUDE		œ
II		ď
1	89	Z
		C
Ö	j	2
1	9	u,
STATION	10 OCT.	AND NOTION NO.
٧,	_	

UPPER AIR DATA 0668003906 WHITE SANDS SITE

WSTM SITE COGRDINATES E 488,580 FEET N 185,045 FEET

TABLE X (Cont)

INDEX OF REFRACTION	1.000051	.0000	.0000	•00000	.0000	.0000	.0000	.00004	•0000	•0000	.00004	°00003	• 00003	.00003	.00003	.00003	.0000	• 00003	.0000	.00003	.00003	£0000°	°0000°	.00002	00000	.0000	.0000	.00002	.00002	.00002
TA SPEED KNOTS	48 • 8	ω ω	φ Φ	.	•	ô	ô	°	ô	ŝ	6	8	ę	2	2،	4 °	ô	٧.	.	œ	~	ည်	÷	2	\$	9	*	•	•	•
WIND DA DIRECTION DEGREES(TN)	257.1	58°	60°	63.	999	65.	64.	64.	65.	99	64.	62.	64.	69	74.	79°	84°	88°	92.	95.	88	78.	79.	98•	~	21.	24.	43.	2	•
SPEED OF SOUND KNOTS	559.0	57.	56.	55.	54.	53.	52°	52°	53.	54.	54,	55.	56.	55°	55.	54.	54.	533	52.	52°	53.	540	550	56.	57°	58°	60.	61.	62°	63.
DENSITY S GM/CUBIC METER	229,3	24.	19.	15.	10.	90	01.	96	90°	85.	80.	75°	70.	99	62.	59.	55.	51.	48.	44.	40.	36.	32.	28.	25.	21.	18.	14.	1], 。	08.
.HUM. CENT	*	* *	# #	¥ ¥	*	* *	* ¥	* *	* *	¥ ¥	* *	* *	¥ *	* *	¥	*	*	* *	¥	*	¥	¥	%	* *	* *	* *	*	* *	* *	* *
EL.H ERCE	•		°	ċ	°0-	-0-	0-	-0-	0	°0-	°	°0-	0-	100	-0-	•0	် ပ	°	0-	-0-	°0-	0	-0°	ဝို	ó	•	°		•	°
α <u>α</u>	9	Ŷ	ĭ	1	,																			Ť	İ	ļ	Ī	ì	Ŷ	i
ERATURE R Dewpoint P Centigrade	ı	!	i	•	•	00	0	•0	•	°	°	•	•	°	°	•	°		°		°	၀	°°	•	•	!	1		ı	
RATURE R DEWPOINT P ENTIGRADE	67.0 0° -	7.8 0	8.6 0	9.4 0.	0.2	1.1 0	0 6	1.6	1.1	0 9 0	0.2 0	0 2.6	9.2	0 9°69	70.0	0.4 0	0.7	1.1 0	1.5	1.9	1.4 0	0.5	0 2.6	8.8	8.0 0.8	.1 0	6.3 0	.0° 1	4,6 0° –	8.
TEMPERATURE R AIR DEWPOINT P EGREES CENTIGRADE	35.7 -67.0 0	32.3 -67.8 0	28.9 -68.6 0	25.7 -69.4 0.	22.6 -70.2 0.	19.5 -71.1 0	6.5 -71.9 0	13.6 -71.6 0.	10.7 -71.1 0	07.9 -70.6 0	05.2 -70.2 0	02.5 -69.7 0.	00.0 -69.2	0 9°69- 4.7	5.0 -70.0 0	2.6 -70.4 0	0.2 -70.7 0	8.0 -71.1 0	5.8 -71.5 0	3.6 -71.9 0	1,5 -71.4 0	9.5 -70.5 0	7.5 -69.7 0	5.6 -68.8 0	3.7 -68.0 0.	1,9 -67.1 0	0.1 -66.3 0	8,4 -65,5 0	6.7 -64.6 0	0 -63.8 0

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. **#**

STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0630 HRS MD1 ASCENSION NO. 824

UPPER AIR DATA 0668003906 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE X (Cont)

INDEX OF REFRACTION	00002	00002	1.000022	.0000s	00000	00002	.00002	.0000	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.0000	°0000	.00001	.0000	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001	1000	0001	0001
ATA SPEED KNOTS	2	-	11,6	2	4	ຕໍ	•	•	რ	ô	•	•	•	G	•	0	•		•	•	9	9	•	•	•	•	•	•		•
WIND DA DIRECTION DEGREES(TN)	21.	56.	226.8	28.	30.	35.	39°	43°	42.	41.	39.	36.	33°	05°	70°	40.	45.	51.	46.	37.	24.	34.	52.	67.	31.	4.	•	2	6	•
SPEED OF SOUND KNOTS	64.	65	565.7	66.	.99	67 °	67.	68°	68.	669	69	°69	70°	20.	71.	71.	720	72°	73°	73.	740	74.	75°	75°	75.	75.	76.	76.	76.	77.
DENSITY GM/CUBIC METER	05°	2	66	7.	4°	2°	ŝ	7°	ហ	ä	-	6	.	ŝ	3	ŗ	6	-	6.	4.	2	-1	9.	ф ф	•	s •	4.	2	1.	ċ
REL.HUM. PERCENT	**		** °0-		-O- **	#* °0-	** •0-	** °0-	** •0-	۰	** •0	## °0−	٥	•	•	•		•	۰	** °0-	•	** •0-	## •0-	₩* •0-	** °0-	** •0−	₩* •0-	** *0-	₩ * 0-	** •0-
ERATURE DEWPOINT CENTIGRADE	0		ဒ်				°						°				_		°								ó			•0
TEMP AIR DEGREES	2	2	-62.1	-	å	•		•	ô	6	ő	ф Ф	æ	ထ	۷,	7.	•	•	•	•	ů	សំ	ស	4.	4°	4.	4.	4.	'n	ຕິ
PRESSURE ILLIBARS	ຕິ	ļ	60°4	6	;	9	4°	å	2	Ť	6	ထိ	7	9	ທິ	4.	ကိ	2°	.	ċ	6	α	ç	•	ŝ	4.	4°	.	2	.
A I																														

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSI. 10 OCT. 68 0630 HRS MDT ASCENSION NO. 824

UPPER AIR DATA 0668003906 WHITE SANDS SITE

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE X (Cont)

INDEX OF REFRACTION	1.000011	1000	1000	0001	1000	0000	0000	00000	00000°	0000	.00000	00000°	.00000	€0000	.00000	.00000	.00000	00000°	.00000	00000	00000°	00000	0000	00000	0000	0000	0000	0000	00000	0000
DATA SPEED) KNOTS	7.8	0	•	•	•	0	0	•	2	4	9	ហ	4°	ကိ	2°	ļ	٦,	•	2°	~	ည့	ô	5	2	9	•	ຜູ	9	÷	Ç
WIND DA DIRECTION DEGREES(TN)	T. 20.	4	•	.	08.	6	02°	ç	-	å	•	6	ç,	01.	2	24.	37.	59.	82,	040	.66	82°	66.	47.	22.	•	ô	2	4.	• 9
SPEED OF SOUND KNOTS	577.2	77°	77.	78.	78°	78.	78.	79.	. 6L	.62	79.	80°	80.	80.	80°	81.	81.	81.	81.	82.	82.	82.	82.	83.	83°	83.	83.	84.	84.	84.
DENSITY GM/CUBIC METER	49.1	/ 0	ę.	ທ່	4.	3	2	ů	ဝံ	ŝ	ထိ	:	ę,	ų,	ŝ	4.	ъ е	ŝ	ŗ.	ů	်	6	ထိ	ф ф	:	.0	•	ۍ.	Š.	40
EN H	*	¥	* *	¥	* #	¥	*	*	*	*	* #	*	∦ ¥	* *	*	*	* *	* *	#	¥ ¥	* *	# *	* *	#	* *	*	*	#	* *	* *
REL.H Perce	0-	°	°	°0-	-0-	0	°°	-0-	0-	°0-	°0-	ဝို	°°	°0-	0	°0-	ç Ç	-0-	°	01	0	0	0	ژ ا	0	°°	-0-	°0-	-0-	°°
FRATURE DEWPOINT CENTIGRADE	°O			° 0		•		ဝိ							ဝ							ဝံ	•	•	၁	-		•		°o
TEMPI AIR DEGREES (ις Ω	'n	ကိ	°	2	2	2°	2°	-	ď	-	l,	<u>.</u>	0	ဝံ	ဝံ	ဝံ	ô	6	0	•	•	•		-48.7	0	0	-48.2	•	-47.8
PRESSURE MILLIBARS	31.0	ċ	6	ထိ	ဆွိ	ç	ę	ę,	ΰ	ر، م	4°	4°	ຕໍ	2°	°	ď	ů	ဝံ	ċ	ŝ	6	ô	æ	ф ф	٧,	۲	ę,	16.6		•

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. **#**

UPPER AIR DATA 0668003906 WHITE SANDS SITE STATION ALTITUDE 3989.0 FEET MSL 10 OCT. 68 0630 HRS MDT ASCENSION NO. 824

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE X (Cont)

INDEX OF OF	1.00000	1.000005	00000	00000	0000	00000	00000	°00000	.00000	.00000	.00000	00000	.00000	° 00000	.00000	0000	00000	00000	00000	00000	.00000	0000	.00000	.00000	00000	0000	00000	0000	0000	00000
SPEED	13°	11.6	6	0	•	0	•	ທີ	4.	'n	2	•	4	က	•	æ	2	-	•	e m	•	о Ф								
WIND DA	112,7	140.1	67.	940	96°	88.	81.	659	27.	6	ļ	ċ	•	2	46.	22。	98.	73.	•	51.	43.	36.								
SOUND	584,	585.1	85.	85°	85°	86.	86.	86.	86.	87°	87.	87.	88.	88.	88.	89.	89.	89.	89.	90°	90.	90°	91.	91.	91.	92.	92.	92.	93.	93.
DENSITY S GM/CUBIC	23,	23,3	2°	2	-	Ļ	ဝံ	ငံ	6	6	å	å	2°	.	.	•	•	S.	ŝ	ŝ	4.	.	4.	÷	÷	8	•	•	•	•
REL.HUM. PERCENT	** **	++ °0−		•	۰	•	** •0-	۰		** •0-	+* •0-	۰		** **	•	•	•	۰	•	•	•	¢	** •0i	** *0-	** •0-	** • G –	₩* •0-	** °0-	** • 0-	** °0-
بر ا	_																													
ERATURE DEWPOIN CFNTIGFA	00	0°	_	°	°o	၀	ဝ	ဝ	•	°0	•	ပ	ဝံ	°o		°	•	ؿ	0	°	° 0	ဝိ	•	•	<u>.</u>	•	•	•	°	°
TURE WPOIN TIGPA	-47.6 0.	4 0	.2 0	0	6.8 0	0 9.9	6.4 0	6.2 0.	0 0.9	5.8	5.6	5,3	5.1 0	4.8	4.6	4°4 0	4.1 0	3°6	3.6	3.4	3.1	2.9	2.6	4.	2.1	0 6°	9•	1.4 0	1.2	0
TEMPERATURE AIR DEWPOIN	15.4 -47.6 0.	1 -47.4 0	4.7 -47.2 0	0 0.4- +0.4	0 -46.8 0	3.8 -46.6 0	3.4 -46.4 0	3.1 -46.2 0	2.8 -46.0 0	2.5 -45.8 0	2.3 -45.6 0	2.0 -45.3 n	1.7 -45.1 0	1.5 -44.8 0	1.2 -44.6 0	1.0 -44.4 0	0.7 -44.1 0	0.5 -43.9 6	.2 -43.6 0	0.0 -43.4 0	.8 -43.1 0	.6 -42.9 0	.4 -42.6 0	.2 -42.4	.0 -42.1	.8 -41.9 0	.6 -41.6	.4 -41.4 0	.2 -41.2 0	.0 -40.9 0

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. # #

STATION ALTITUDE 3989.0 FEET MSL 0630 HRS MDT 824 10 OCT. 68 ASCENSION NO.

0668003906 WHITE SANDS SITE MANDATORY LEVELS

WSTM SITE COORDINATES E 488,580 FEET N 185,045 FEET

TABLE XI

12	KNOTS	•	•	•		6	'n.	21.5	-	.	1:	.	2	•	?	•	2	е 6	•	4	4.	;	•	•	•	.	ຜ	•	'n
WIND	S	27.	67.	81.	98.0	21.8	36.8	8	34.2	37.3	36.4	40.8	44.2	50.6	52.6	54.2	54.1	64.3	64.4	81.7	24.5	27.2	40,	36.	4.	æ	95.	4.	50.
REL.HUM.			61,					18.						***	***0-	***0-			***0-	****	***01	* * ° O -	**°0"	***01	***0-	***0-	**°01	***0-	* * · O -
ERATURE DEWPOTNT	NTIGRA	•	4.0	•		•		-23.3	•	31.	37.	•	•	•	ċ	•		0		•		•	•	°	·	ဝံ	°	°	°
	DEGREES	ຕໍ	•	2	•	•	9	-2.1	2	လုံ	8	Š	ຜູ້	÷	•	•	9	. 69	6	•	9	å	6	\$	8	-	÷	۰	•
GEOPOTENTIAL	FEET	02		4	036	2	448	17	923	190	482	804	164	573	40524.	328	639	000	434	868	131	441	813	275	880	267	744	365	52
PRESSURE GE	MILLIBARS	50	00	50	00	50	00	550.0	00	50	00	50	00	50	00	52	20	25	00	0	0	0	0	0	0	S.	0	S	

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION. ∦ **₩**

As a select a same when a selection of

			72	~	~	~	(-)	(:)	
MPACT) (S)	E-W	MS * ST	13.5W	M9.9	2.4W	1.9E	38.8	1.98
THEORETICAL IMPACT	(IN MILES)	N-S	71.24	09.69	68.8N	70.3N	71.4N	65.0N	65.4N
THEORE	<u> </u>	RANGE	72.8	70.9	69.1	70.3	71.4	65.1	65.4
AZI-	-58G)	REES)	347.8	349.0	354.5	358.0	001.5	003.3	001.7
ND	TOTAL	M-E	76.0W	24.0W	17,1W	12.9W	8.6W	6.7W	8.64
пто ит	TO	N-S	14.78	16.38	17.18	15.68	14.58	20.98	20.58
MILL'S DI	4000-69330 FT	E-W	30.64	30.6W	30.64	30.6W	30.6W	30.6W	32.5W
MENT IN	9-0007	N-S	3.28	3,28	3.28	3.25	3.25	3.28	2.88
DISPLACE	00 FT	E-W	3.8E	3.5E	9E.9	10.4E	12.8E	14.2E	14.2E
SECOND-STAGE IMPACT DISFLACEMENT IN MILL'S DUE TO WIND	216-4000 FT	N-S	10.25	10.28	9.28	9.18	8.48	12.28	12.28
ND-STAG	15-216 FT	E-W	0.8E	3.1E	9°.9	7.3E	9.2E	9.7E	9.7E
SEC	15-21	N-S	1 38	2.98	4.78	3.38	2.98	5.58	5.58
TIME	ĵ.	PIBAL	0520	0530	0545	0610	0620	0630	0630
RELEASE TIME	(MOL)	RAWIN-	0330	0330	0330	0330	0330	0330	0630

	164			
	MUTH MUTH	MILES FROM LAUNCHER	FROM LA	UNCHER
	REES)	RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 84.0 DEGREES QE)	010.0	010.0 87.2 85.9N 15.4E	85.9N	15.4E
NO WIND IMPACT	002.0	007.0 86.5	85.9N	10.5E
PREDICTED SECOND-STAGE IMPACT	357.0	357.0 70.0 69.9N	69.9N	3.7W
SECOND-STAGE IMPACT, RADAR TRACK	015.7	015.7 84.4	81.2N	22.8E
PREDICTED BOOSTER IMPACT	040.0	040.0 1.5	1.1N	1.0E
ACTUAL BOOSTER IMPACT	V/N	N/A	V/N	N/N

TABLE XII. IMPACT PREDICTION DATA NIKE-HYDAC STV, SR-076

BLANK PAGE

UNCLASSIFIED

			و ما در			
	NTROL DATA - R		•			
(Security classification of title, body of abstract and indexi						
1. ORIGINATING ACTIVITY (Corporate author)		20. REPORT SECURITY CLASSIFIE UNCLASSIFIE				
U. S. Army Electronics Command						
Ft. Monmouth, New Jersey		25. GROUP				
		<u> </u>				
3. REPORT TITLE						
Armionological Dimi Droops Nill Pithia	cmr. cp. 07/					
METEOROLOGICAL DATA REPORT, NIKE-HYDAC	51V, 5K-076					
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)						
		· · · · · · · · · · · · · · · · · · ·				
S. AUTHOR(S) (First name, middle initial, last name)						
Len E. Carter						
Len E. Carter						
November 1968	74. TOTAL NO. 01	F PAGES	75. NO. OF REFS NONE			
		<u></u>				
SE CONTRACT OR GRANT NO.	Se. ORIGINATOR'S	REPORT NUM	(3)			
	DR-369					
b. Project no.	DX-309					
	ļ					
^{c.} DA Task 1T665702D127-02	95. OTHER REPORT NO(\$) (Any other numbers that may be assignated this report)					
d.						
This document is subject to special ex	nort controls	and each i	ransmittal to foreign			
governments or foreign nationals may be	e made only wi	th prior a	approval of Atmospheric			
Sciences Research Office, White Sands l	Missile Range.	Non Mouri				
		NEW MEXIC	20.			
11. SUPPLEMENTARY NOTES	12. SPONSORING	HILITARY ACT	IVITY			
	U. S. Ar	my Electro	onics Command			
	U. S. Arm	my Electro ric Science	onics Command ces Research Office			
11. SUPPLEMENTARY NOTES	U. S. Arm	my Electro ric Science	onics Command			
	U. S. Arm	my Electro ric Science	onics Command ces Research Office			
11. SUPPLEMENTARY NOTES	U. S. Arm	my Electro ric Science	onics Command ces Research Office			
11. SUPPLEMENTARY NOTES	U. S. Arm	my Electro ric Science	onics Command ces Research Office			
11. SUPPLEMENTARY NOTES 13. ABSTRACT 4	U. S. Ar Atmosphe White Sa	my Electro ric Science nds Missi	onics Command ces Research Office le Kange, New Mexico			
13. ABSTRACT Meteorological data gathered for	U. S. Arr Atmosphe White Sa	my Electronic Science of Nike-H	onics Command ces Research Office le Kange, New Mexico			
Meteorological data gathered for are presented for the Space and Missil	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			
Meteorological data gathered for are presented for the Space and Missil and for ballistic studies. The data a in tabular form.	U. S. Arm Atmosphe White Sa the launching e Systems Orga	my Electrony Electrony Electrony Electrony Missississississississississississississ	onics Command ces Research Office le Range, New Mexico ydac STV, SR-076, Greenbelt, Maryland,			

UNCLASSIFIED Security Classification

UNCLASSIFIED

	Security Classification		LINKA					
14.	_	KEY WORDS			LINI		LIN	
			HOLE	WT	ROLE	WT	ROLE	WT
		i	1 1		Į	1	· 1	
		i i	1	1		¹	· }	
	1	Ballistics	1 1			1	· }	
			1 1	 	1	·	· }	1
	_	Vatarnal	1 1	}]	1	1 }	1	1
	2.	Meteorology	1 1	1		1	1	1
			1	\ \		1 1	1	
	3.	Wind	q 1	ļ i	İ	1 1	1	1
			ł. I	1	1 1	1	1	
			1 1	1 1	l i	· 1	1	
			1 1	! !) i	1 1	1	١ !
			1	1 j	\ i	ļ ļ	, j	1
			1	ļ i	į į	! I	!!	Į į
			(]	ļ i	,	1	Į į
			1 1	Į į	ļ l	1 1	1	1
			•	}	1 1	1 1	1 1	ļ
			† \	۱ ۱		1)	1 1	ļ
			(ţ	1 1	ę l	1	[
ſ			[1	ţ l	ţ i	ţ i	ţ Ì
			()	1 1	Į l	1 1	Į l	ا ا
			1 :	l 1	[1 1	ŧ i	1
			1	l	ş Ι	1	1 1	1
				 	1	1	i i	1
				Į	¶	!	1	ţ
			(1	,	1	! !	[
			[.	(•	1 1	•
			1	(į į	()	!	į į
			[ļ ·	i	1	(!
					{	! :	ļ ,	•
			İ])	(1	ł
			{	[!	(!	į
			1	1	1	1 :	(Ī
			1	1	Į i	† 5		l
			1	[{	(l
			1	1		()		ļ
		•	1	1	ļ	()	(1
		•	ì	1	1	1		1
			1	[[ł
		•	1		1	1	١ .	1
				į i	1		()	ì
			1	}	1	{	{	Į.
			1	1		1	[,	İ
			1	1	1	1	1	
			1	1	[.	1	1	1
			1	1	1	1		1
			1	1	1	1		i
			1	1	1	1	1	ſ
			1	1	1	1		1
			1	1	j		[1
			}	1	1	1		}
		•	1	1	1	1	1	ŀ
			1	1	Į.	1	[ļ
		*	1	1	1	1	1	l
			1	1	1	1	1	ł
			i	1	1	1	1	1
			ļ	1	1	1	}	1
			1	1	1	1	1	}
			1	1	1	ł	1	1
			ļ	1	1	1	1	1
			1	1	1	1	1	1
			1	î		1	1	1
			1	<u> </u>	L	L	L	

UNCLASSIFIED

Security Classification